

SPECIFICATIONS

MOBILE GENERATOR SPECS



Spec	25 kVA	45 kVA	65 kVA	125 kVA
Prime power	25 kVA / 20 kW	45 kVA / 36 kW	65 kVA / 51 kW	125 kVA / 100 kW
Standby power	27.5 kVA / 22 kW	48.5 kVA / 38.8 kW	69.3 kVA / 55.4 kW	137.5 kVA / 110 kW
Engine	Isuzu 4LE2T	Isuzu 4LE2X	Isuzu 4JJ1X	Isuzu BR-4HK1X
Fuel tank	51.5 gal	80.5 gal	111 gal	168 gal
Runtime at full load	32 hrs	28.75 hrs	28.5 hrs	23.3 hrs
Sound (no load / full)	57 / 63 dBA	57 / 61 dBA	63 / 69 dBA	61 / 67 dBA
Max amps, 3-phase 208V	65 A	119 A	167 A	328 A
Operating weight	2,205 lbs	3,337 lbs	4,189 lbs	6,702 lbs
Size on trailer (L x W x H)	119" x 54" x 62"	144" x 70" x 73"	160" x 74" x 84.25"	196" x 79" x 85"
Emissions	Tier 4 Final	Tier 4 Final	Tier 4 Final	Tier 4 Final

All models: single-phase 120/240V and 277V; three-phase 208/240V and 416/480V; automatic voltage regulation $\pm 0.5\%$; 110% fluid containment. Sound measured at 23 ft.

WHEN DOODIE CALLS, WE ANSWER.

844-444-POOP (7667)