

SPECIFICATIONS

MOBILE GENERATOR SPECS



MODEL	25 kVA Airman SDG25S	45 kVA Airman SDG45S	65 kVA Airman SDG65S	125 kVA Airman SDG125S
POWER OUTPUT				
Prime power	20 kW	36 kW	51 kW	100 kW
Standby power	27.5 kVA / 22 kW	48.5 kVA / 38.8 kW	69.3 kVA / 55.4 kW	137.5 kVA / 110 kW
Max amps, 3-phase 208V	65 A	119 A	167 A	328 A
Engine	Isuzu 4LE2T	Isuzu 4LE2X	Isuzu 4JJ1X	Isuzu BR-4HK1X
FUEL & RUNTIME				
Fuel tank	51.5 gal	80.5 gal	111 gal	168 gal
Runtime at full load	32 hrs	28.75 hrs	28.5 hrs	23.3 hrs
SIZE & WEIGHT				
Size on trailer L x W x H	119" x 54" x 62" about 10' long	144" x 70" x 73" about 12' long	160" x 74" x 84.25" about 13'4" long	196" x 79" x 85" about 16'4" long
Operating weight	2,205 lbs	3,337 lbs	4,189 lbs	6,702 lbs
SOUND & EMISSIONS				
Sound at 23 ft no load / full load	57 / 63 dBA	57 / 61 dBA	63 / 69 dBA	61 / 67 dBA
Emissions	Tier 4 Final	Tier 4 Final	Tier 4 Final	Tier 4 Final
Single-phase: 120/240V and 277V Three-phase: 208/240V and 416/480V Voltage regulation: ±0.5%, automatic Containment: 110% for fuel, oil & coolant				

WHEN DOODIE CALLS, WE ANSWER.

844-444-POOP (7667)